

Idenden T303

SELF-ADHESIVE BRIGHT FOIL TAPE

Date: 19 August 2020

Fact Sheet No.: TDS00654

YOUR SMART ADVANTAGES

- Fire tested
- Consistent performance
- High tack adhesive

USES

Bostik T303 Self-Adhesive Bright Foil Tape is a market-leading product for the heating, ventilation and air conditioning and asbestos abatement sectors. The high standards of reliability, strength and durability mean it is used for diverse applications in many other sectors, for example process plant, marine and offshore. Bostik T303 is manufactured to the highest specifications and is coated with a high tack rubber/resin adhesive system and protected by a removable release paper.

Bostik T303 provides excellent performance, maintaining insulation efficiency by protecting against the effects of fire, moisture and dust. It is easy to apply, exhibiting instant adhesion and can be moulded to any profile. The final bond has high shear strength and the foil promotes the optimum balance of surface conformity and tensile strength. This makes it ideal for lap sealing foil faced insulation materials, metal and duct sealing, asbestos abatement tenting and other general-purpose applications.

PRODUCT CHARACTERISTICS

Finish	Bright aluminium foil	
Adhesive	Rubber/resin	
Release Paper	High quality siliconised paper	
Product Code	30140160	45m x 50mm x 24
	30140161	45m x 75mm x 16
	30812998	45m x 100mm x 12

Storage/Shelf Life

Store for up to 12 months from date of manufacture when stored in original, unopened packaging under cool, dry conditions within the temperature range +10°C to +30°C and out of direct sunlight.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature

Above +5°C

Service Temperature

-10°C to +90°C
(depending on operating conditions)

Ultimate Tensile Strength

Approximately 90 N/25mm²
(aluminium only)

Elongation

Minimum 7%
(approx. - aluminium only)

Peel adhesion to steel

Initial: 20 - 25 N/25mm
24 hours: 25 - 30 N/25mm
(approx.)

Fire Tests

Independently tested to BS 476:
Part 6 - Pass
Part 7 - Class 1
Building Regulations: Class 0
When tested as supplied and applied to calcium silicate board. Results will vary when applied to other substrates.

UL classified

General Use Tapes

R38033

Surface burning characteristics for



	<p>building materials UL723</p> <p>Applied to inorganic reinforced Cement board+</p> <p>Flame spread 5</p> <p>Smoke developed 15</p> <p>+ - Tested in two 102 mm (4 in.) wide longitudinal strips spaced 203 mm (8 in.) OC. (Tape coverage: 44 percent of the exposed test sample area.)</p> <p>Bostik T303 Self-Adhesive Bright Foil Tape meets the requirements of NFPA 90A and 90B (2018 edition) for a flame spread index of less than 25 and a smoke developed index of less than 50 when tested to ANSI/UL 723, Standard for Test for Surface Burning Characteristics of Building Materials by Underwriter's Laboratories.</p>
VOC Testing	<p>Bostik T303 Self-Adhesive Bright Foil Tape showed low VOC contents in a test specified in LEED 2009 EQ c 4.1 (adhesives and sealants). The VOC content is below the limit value specified as 30 grams/litre (less water) for 'Metal to Metal Adhesives':</p> <p>VOC g/l: 2</p>

instance, insulation should be fixed using a suitable adhesive or hanger system.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik T303 Self-Adhesive Bright Foil Tape, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



DIRECTIONS FOR USE

IMPORTANT: Before using Bostik T303 Self-Adhesive Bright Foil Tape, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. Surfaces to be bonded must be clean, dry and free from dust, grease and loose materials. If necessary, wipe surfaces sparingly with a cloth dampened with a ketone-free cleaner such as EVO-STIK Cleaner 4 and allow to dry for at least an hour before tape application.
2. The butt joints of insulation sections should be positioned together without gaps to ensure an adequate bond.
3. Select a tape width suitable for the application. A width of 50mm is suitable for closely positioned, flat sections. Otherwise, select a tape the thickness of the insulation plus 50mm to allow for the exposed cut edge.

APPLICATION

4. Remove the release paper from a section of the tape, taking care not to touch the adhesive surface. Align the tape centrally over the joint. Pull the tape taut and then press down well over the entire joint area. Rub the tape to remove any wrinkles or folds.

PRECAUTIONS IN USE

Bostik T303 Self-Adhesive Bright Foil Tape is intended for joint sealing applications only, and is therefore not suitable for use where the joint is subject to mechanical stress. In this

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com