



## British Gypsum fixing products

High performance,  
maximum productivity

# British Gypsum fixing products

An essential part of our high performance systems, British Gypsum screws are designed for optimum fixing strength and reliability.



## British Gypsum fixings range

### Board-to-metal and board-to-timber fixings



#### Drywall Screws

Corrosion-resistant self-tapping zinc plated steel screws with countersunk cross head.

**Tip:** Self-tapping

**Head:** Countersunk cross

**Coating:** Black / Phosphate

**Application:** Plasterboard to metal framing profiles less than 0.8mm gauge and 'I' studs  $\leq 0.6$  gauge, and timber studs/support.

**Available lengths (mm):** 25, 35, 40, 45, 50, 55, 60, 65, 75, 80, 90, 105, 120



#### Collated Drywall Screws

Strips of collated Drywall Screws supplied in boxes of 1000 screws (20 strips).

**Tip:** Self-tapping

**Head:** Countersunk cross

**Coating:** Black / Phosphate

**Application:** Plasterboard to metal framing profiles less than 0.8mm gauge and 'I' studs  $\leq 0.6$  gauge, and timber studs/support.

**Available lengths (mm):** 25, 35, 40, 45, 50



#### High Performance Screws for use with Gyproc Habito

Specifically designed for use with Gyproc Habito; featuring a unique lipped head to ensure easy finishing.

**Tip:** Self-tapping

**Head:** Countersunk cross

**Coating:** Black phosphate

**Application:** Gyproc Habito board to metal framing sections  $< 0.8$ mm gauge and 'I' Studs  $\leq 0.6$ mm gauge; and to timber studs / supports

**Available lengths (mm):** 25, 35, 40, 50

### Metal-to-metal fixings



#### Wafer Head Jack-Point Screws

Similar to British Gypsum Wafer Head Drywall Screws but featuring a self-drilling tip.

**Tip:** Self-tapping

**Head:** Wafer cross

**Coating:** Zinc

**Application:** Metal to metal framing  $\geq 0.8$ mm gauge or 'I' Studs  $\geq 0.6$ mm gauge

**Available lengths (mm):** 13



#### Jack-Point Screws

Corrosion-resistant self-drilling zinc plated steel screws with countersunk cross head.


**Tip:** Self-drilling

**Head:** Countersunk cross

**Coating:** Zinc

**Application:** Plasterboard to metal framing  $\geq 0.8$ mm gauge and 'I' Studs  $\geq 0.6$ mm gauge

**Available lengths (mm):** 25, 35, 41, 60



#### Wafer Head Drywall Screws

Corrosion-resistant self-drilling zinc plated steel screws with countersunk cross head.

**Tip:** Self-drilling

**Head:** Countersunk cross

**Coating:** Zinc

**Application:** Metal to metal less than 0.8mm gauge

**Available lengths (mm):** 13

## Specsure® lifetime system warranty

British Gypsum fixings form part of this unique “off the shelf” warranty to end users that confirms British Gypsum proprietary systems will perform to the parameters published in our current literature.



## To qualify for SpecSure®

Just specify and install British Gypsum Systems in line with recommendations in the current British Gypsum **White Book** available to download from [british-gypsum.com](http://british-gypsum.com)


The system must comprise only genuine branded British Gypsum components, tried and tested over many decades in some of the UK's most prestigious buildings. We cannot guarantee that the use of other manufacturers' components will meet our rigorous performance and quality standards when installed in our tested systems.

## Conformity to EN standards

British Gypsum fixings conform to *EN 14566*.

*EN 14566* is the European standard that specifies the characteristics and performance requirements of mechanical fasteners used for fixing gypsum plasterboard and specialist boards to timber and metal. The standard also specifies the requirements for fixings that may be used in the construction of metal framing and joining of metal components.

## Specialist fixings



### Nailable Plugs

Combination of masonry nail and plastic wall fixing with expanding tip and countersunk head.

**Tip:** Nail

**Head:** Countersunk

**Coating:** Zinc

**Application:** Secondary fix for Gyproc ThermaLine laminates

**Available lengths (mm):** 60, 80, 100, 110, 120, 135



### Rigidur H Screws

Corrosion-resistant self-tapping zinc plated steel screws with countersunk cross heads.

**Tip:** Self-tapping

**Head:** Countersunk cross

**Coating:** Zinc

**Application:** Rigidur H board to metal framing less than 0.8mm gauge

**Available lengths (mm):** 30, 40



### Rigitone Screws

Corrosion-resistant quick-fit self-tapping black phosphate screws with countersunk cross heads designed to fix Rigitone Boards.

**Tip:** Self-tapping

**Head:** Countersunk cross

**Coating:** Black

**Application:** Rigitone ceiling boards to CasoLine MF and Gyproc UNIVERSAL systems

**Available lengths (mm):** 30



### Glasroc F FIRECASE Screws

Specifically designed for board-to-board fixing of Glasroc F FIRECASE board in the FireCase system, the screw have a unique head design that countersinks into the board allowing easy finishing.


**Tip:** Self-tapping

**Head:** Countersunk cross

**Coating:** Zinc

**Application:** Glasroc F FIRECASE board to metal framing

**Available lengths (mm):** 40, 50, 58, 70



### GypFloor SILENT Floor Screws

Providing support for the GypFloor SILENT acoustic floor system.

**Tip:** Self-tapping

**Head:** Countersunk cross

**Coating:** Zinc

**Application:** GypFloor SILENT

**Available lengths (mm):** 55

“Gyproc”, “Thistle”, “Gypframe” and “Glasroc” are all registered trademarks of Saint-Gobain Construction Products UK Limited. “Isover” is a registered trademark of Saint-Gobain Isover and “Artex” is a registered trademark of Saint-Gobain Construction Products UK Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, Binley Business Park, Coventry, CV3 2TT, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: [british-gypsum.com](http://british-gypsum.com). For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

“British Gypsum” is a registered trademark of Saint-Gobain Construction Products UK Limited.



**Technical enquiries**  
British Gypsum  
Technical Advice Centre  
East Leake  
Loughborough  
Leicestershire  
LE12 6HX

Telephone: 0115 945 6123  
Fax: 0115 945 1616  
Email: [bgtechnical.enquiries@bpb.com](mailto:bgtechnical.enquiries@bpb.com)

Training enquiries: 0844 561 8810

British Gypsum May 2016 BG-FDS-03

**[british-gypsum.com](http://british-gypsum.com)**

