



**FIREFLY™ Collaroll** is a lightweight flexible fire rated penetration collar used to seal penetrations through **FIREFLY™** fire barriers enabling the integrity of the fire barrier to remain intact. **FIREFLY™ Collaroll** should be used with **FIREFLY™** barriers as part of a system.

DESCRIPTION	Lightweight, flexible penetration collar with flange – integrity only
BASE FABRIC	Woven fibreglass fabric, with high temperature finish
THICKNESS OF MATERIAL	1.3mm
INTEGRITY	60 minutes minimum
LENGTH	10 metres
WEIGHT	5.1 kg / Roll
SLEEVE WIDTH	300mm
FLANGE	90mm
BUILDING REGULATIONS, FIRE PROPAGATION TEST	Class "0" rating
FIREFLY™	<p>All <b>FIREFLY™</b> cavity barrier products must be installed in compliance with the <b>FIREFLY™</b> Installation Guide, which is provided upon request. Deviation from these drawings should not be carried out without written authority from the <b>FIREFLY™</b> Technical Department.</p> <p>All figures quoted are nominal, believed to be true at the time of printing and are presented without guarantee. It is up to the user to determine the suitability of use.</p>

## Advanced Materials for Demanding Environments

05/21-1

E [info@tbafirefly.com](mailto:info@tbafirefly.com) T +44 (0) 1706 758817 W [tbafirefly.com](http://tbafirefly.com)

**TBA**   
Protective Technologies Ltd