


## U Protect for fire, thermal and acoustic insulation of ventilation and smoke extraction ducts



### FIRE RESISTANCE

Passive fire protection system



### FAST INSTALLATION

Thanks to its light weight and high flexibility, it can be installed by one person without any special equipment

U Protect system is designed to provide fire resistant, an easy to install, lightweight and efficient thermal and acoustic insulation solution in HVAC for circular and rectangular ventilation and smoke extraction ducts up to EI 120.

ISOVER Fire Protect Screws are part of ISOVER U Protect fire resistant solution. Installation guidelines must be followed and all ISOVER U Protect components used.



CHARACTERISTIC	SYMBOL	UNIT	QUANTITIES AND DECLARED VALUES	STANDARD
Reaction to fire	-	-	Non combustible, Euroclass A1 (as part of system)	-
Application field	-	-	ISOVER Fire Protect Screw is part of ISOVER U Protect fire resistant solution up to EI120 for ventilation and smoke extraction ducts	EN 1366-1 EN 1366-8
Material	-	-	Metal	-

[www.isover-technical-insulation.com](http://www.isover-technical-insulation.com)

*The technical information corresponds to our present state of knowledge and experience at the date of printing (see imprint). But no legal guarantee can be given, unless it has been explicitly agreed. The state of experience and knowledge is developing continuously. Please see to it that you always use the latest edition of this information. The described product applications do not take special circumstances in consideration. Please verify whether our products are appropriate for the concrete application. For further information please contact our Isover sales offices. We deliver only according to our terms of trade and terms of delivery.*

SAINT-GOBAIN ISOVER · Tour Saint-Gobain, 12 place de l'Iris · 92096 La Defense Cedex · France